Ford Bronco Rear Lower Control Arm Instructions

www.TERAFLEX.com

 # 1836010



Important Notes:

Prior to beginning this install, or any installation, read the instructions thoroughly to familiarize yourself with the required steps. Evaluate if you are experienced and capable to personally perform these modifications. A factory service manual should be used in conjunction with these installation instructions.

This product will change the highway handling characteristics of your vehicle, exercise caution. After altering the suspension it is always advisable to have an alignment done by a competent 4 wheel drive shop or by an alignment shop that is experienced with lifted 4 wheel drive vehicles.

Refer to the parts list to ensure that all necessary components and hardware has been included. If any parts are missing please contact your local TeraFlex dealer for assistance.

When reinstalling OEM hardware, refer to the torque specs given in the Factory Service Manual.

Tools Needed:

- **Metric Sockets and Open End Wrenches**
- **General Mechanics Tools**
- **Transmission Jack**
- **Torque Wrench**
- **Factory Service Manual**
- **Torx Plus (TP-25)**



1836010 - Ford Bronco Rear Lower Control Arm (Pair)			
Item #	Part No.	Description	QTY
1	07-01-006-320	Suspension Link (S), Control Arm, Ford Bronco, Rear / Lower / Left Assembly	1
2	07-01-006-330	Suspension Link (S), Control Arm, Ford Bronco, Rear / Lower / Right Assembly	1

DUE TO THE BOLT LOCATIONS OF THE CONTROL ARMS ON THE FRAME, REMOVAL OF THE GAS TANK IS NECESSARY. IT IS EASIEST IF THE TANK IS 1/4 OR LESS FULL WHEN REMOVING FOR LIGHTER WEIGHT

LIFT BRONCO AND SUPPORT AT THE FRAME
DISCONNECT FUEL TANK FILLER NECK AND FUEL LINE FROM FUEL TANK



1

REMOVE FUEL TANK

SUPPORT FUEL TANK WITH A TRANSMISSION JACK

IF THERE IS A SKID PLATE, REMOVE SKID PLATE BOLTS

LOWER THE TANK A LITTLE AND SECURE FUEL TANK TO TRANSMISSION JACK WITH A RESTRAINING STRAP

NOTE: TAKE CARE NOT TO STRAIN FUEL LINES AND WIRING HARNESS WHEN LOWERING FUEL TANK

2

AT TOP OF THE FUEL TANK DISCONNECT FUEL TANK WIRING HARNESS



3

AT THE TOP MIDDLE OF THE FUEL TANK DISCONNECT 2 FUEL LINES



4

AT THE TOP FRONT OF THE FUEL TANK DISCONNECT 2 FUEL LINES AND LOWER THE FUEL TANK



DISCONNECT ANY ADDITIONAL LINES OR WIRING HARNESSES FROM THE FUEL TANK AS NEEDED

LOWER THE FUEL TANK FROM THE BRONCO AND SECURE FUEL TANK IN A SAFE LOCATION

5

REMOVE PASSENGER REAR LOWER CONTROL ARM BOLT COVER AT THE FRAME



6

REMOVE PASSENGER SIDE REAR LOWER CONTROL ARM





SUPPORT THE AXLE AT THE PINION WHEN REMOVING CONTROL ARMS

7

INSTALL NEW PASSENGER SIDE REAR LOWER CONTROL ARM



STICKER FACES OUTWARD TOWARD FRONT OF VEHICLE



8

REMOVE DRIVER SIDE REAR LOWER CONTROL ARM





9

INSTALL NEW DRIVER SIDE REAR LOWER CONTROL ARM





10

IR BUSHING ALLOW THE HARDWARE TO BE TIGHTENED WHIL THE VEHICLE IS STILL IN THE AIR.

REINSTALL PASSENGER REAR LOWER CONTROL ARM BOLT COVER AT THE FRAME



11

IF INSTALLING 1836020 REAR UPPER CONTROL ARMS DO SO NOW BEFORE REINSTALLING THE FUEL TANK

LIFT FUEL TANK BACK UNDER BRONCO AND RECONNECT THE 4 FUEL LINES AT THE TOP OF FUEL TANK



12

AT THE TOP OF THE FUEL TANK RECONNECT FUEL TANK WIRING HARNESS



TORQUE SKID PLATE
59 FT. - LBS.
BOLTS 18mm

IF SKID PLATE WAS PRESENT,
REINSTALL BOLTS

13

RECONNECT FUEL TANK FILLER NECK AND FUEL LINE TO FUEL TANK



LOWER BRONCO TO THE GROUND

TO COMPLETE INSTALL A WHEEL ALIGNMENT WILL BE NECESSARY

14

MAINTENANCE INFORMATION:
It is the buyer's responsibility to have all suspension, drivetrain, steering, and other components checked for proper tightness and torque after the first 100 miles and every 3000 miles after that.

NOTICE TO INSTALLER:
The enclosed "Warning to Driver" sticker must be installed in the vehicle in driver's view. This sticker is to act as a constant safety reminder when operating the vehicle. It is your responsibility as the equipment installer to install the provided sticker and to forward the product instructions to the vehicle's owner for review. If a "Warning to Driver" sticker or product installation guide were not included in the kit, FREE replacement stickers and instructions are available by request. It is the installer's duty to ensure a safe and controllable vehicle after the modifications have been performed.

WARNING TO DRIVER:
This vehicle has been modified to enhance off road performance and has unique handling characteristics. Use in harsh environments can cause extreme stress on the components. Vehicle should be inspected after being off road to make sure that all the components are in working order and safe to travel on the highway. All fasteners should be checked so that they are at the correct torque specifications as the vibration and stresses from off roading may cause critical fasteners to work loose. Extra care should be taken to inspect the critical components, steering, and brake systems. During each oil change components such as arms, tie rod ends, etc should be greased and checked for excessive wear. Any worn components should be replaced. When returning to the pavement always set or restore tire air pressure to the factory recommendation and connect or engage any disabled sway bar mechanisms. Because of the higher center of gravity and larger tires, this vehicle handles and reacts differently than many passenger cars, both on and off road. You must drive it safely! Extreme care should be taken to prevent vehicle rollover or loss of control, which can result in serious injury or death. Avoid sudden sharp turns or abrupt maneuvers. Generally, braking performance and capabilities are decreased when significantly larger/heavier tires are used, especially when used in combination with transfer case low-range reduction kits. Take this into consideration while driving. Do not add, alter or fabricate any factory or aftermarket parts to increase vehicle height over the intended height of the TeraFlex product purchased. Mixing component brand is not recommended. TeraFlex Inc. will not be responsible for any altered product or any improper installation or use of our products. We will be happy to answer any questions concerning the design, function, and correct use of our products. It is ultimately the buyer's responsibility to have all bolts/nuts checked for tightness after the first 100 miles and then every 3000 miles. Wheel alignment, steering system, suspension and drive line systems must be inspected by a qualified professional mechanic at least every 3000 miles.

TERAFLEX LIMITED WARRANTY:
THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY ALSO HAVE OTHER RIGHTS, WHICH VARY FROM STATE TO STATE. THE LIMITED WARRANTY CAN ALSO BE FOUND ONLINE AT WWW.TERAFLEX.COM/WARRANTY OR IN THE DOCUMENTATION WE PROVIDE WITH THE PRODUCT. WE WARRANT THAT DURING THE WARRANTY PERIOD, THE PRODUCT WILL BE FREE FROM DEFECTS IN MATERIALS AND WORKMANSHIP. WE LIMIT THE DURATION AND REMEDIES OF ALL IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE TO THE DURATION OF THIS EXPRESS LIMITED WARRANTY. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. OUR RESPONSIBILITY FOR DEFECTIVE GOODS IS LIMITED TO REPAIR, REPLACEMENT OR REFUND AS DESCRIBED BELOW IN THIS WARRANTY STATEMENT.

WARNING: Neither TeraFlex, Inc. nor the seller will be liable for any loss, damage, or injury directly or indirectly arising from the use of or inability to determine the use of these products. Before using, the user shall determine the suitability of the product(s) for its intended use(s), and the user shall assume all responsibility and risk in connection therewith.

WHO MAY USE THIS WARRANTY?
TeraFlex, Inc. ("we") extend this limited warranty only to the consumer who originally purchased the product ("you"). It does not extend to any subsequent owner or other transferee of the product.

WHAT DOES THIS WARRANTY COVER?
This limited warranty covers defects in materials and workmanship of the TeraFlex product purchased by you (the "product") for the Warranty Period as defined below.

WHAT DOES THIS WARRANTY NOT COVER?
This limited warranty does not cover any damage due to: (a) transportation; (b) storage; (c) improper use; (d) failure to follow the product instructions or to perform any preventive maintenance; (e) modifications; (f) unauthorized repair; (g) normal wear and tear; (h) product finish; (i) improperly installed or applied products; (j) improperly maintained products; (k) products used for any racing or competition; or (l) external causes such as accidents, abuse, neglect or other actions or events beyond our reasonable control. The following will VOID the warranty: (a) improper installation; (b) failure to properly maintain product; (c) use of product for racing or competition; (d) neglect or abuse.

WHAT IS THE PERIOD OF COVERAGE?
This limited warranty starts on the date of your purchase and lasts as set forth below (the "Warranty Period"). The Warranty Period is not extended if we repair or replace the product. We may change the availability of this limited warranty at our discretion, but any changes will not be retroactive. All of the foregoing warranties are limited to the original purchaser and the original vehicle the product was installed on:

Lifetime Warranty:
- The following suspension components: coil springs, bump stops, control arms, track bars, sway bars & links and IR bushings
- 9550 Shocks: shocks & stabilizer
- The following steering components: ball joint, tie rod, drag link, tie rod ends, big brake kit, big rotor kits and brake lines.
- The following body armor components: skid plates, racks, Alpha carrier & components, and cb mounts.
- Wheels & wheel adapter spacers.

3 Year Warranty:
- Delta Brake Kit.
- Transfer Case; short shaft kits, 2WD low range.
- ST Dual Rate Pneumatic Front Sway Bar.

1 Year Warranty:
- Falcon Shocks: all Falcon products including 1 series, 2 series, and 3 series shocks, as well as Nexus series stabilizers
- Axle Assemblies & Axle Housings: Tera60, CRD60, Tera44, Tera30, inner & outer knuckles, axle shafts and full float conversion kits.
- Bushings: Alpine control arm and track bar (does not include IR).
- Driveshaft & Driveshaft Components: CV driveshafts, Rzeppa CV kit and yokes.
- Recovery Equipment: tow strap, tree strap and d-rings.

90 Day Warranty:
- Paint & powder coat finishes: defect coverage only - does not cover any standard aesthetic wear caused by use/abuse.

No Warranty:
- Wearable items; brake rotors, brake pads.

WHAT ARE YOUR REMEDIES UNDER THIS WARRANTY?
With respect to any defective product during the Warranty Period, we will, in our sole discretion, either: (a) repair or replace such product (or the defective part) free of charge or (b) refund the purchase price of such product. We will also pay for shipping and handling fees to return the repaired or replacement product to you if we elect to repair or replace the defective product.

HOW DO YOU OBTAIN WARRANTY SERVICE?
To obtain warranty service, call our Customer Service Department at (801) 713-3314, Monday – Friday, 8:00 AM – 5:00 PM MST. Closed Saturday, Sunday & all major holidays. All returns must be accompanied by proof of purchase or original invoice. It is the customer's responsibility to remove the product from the vehicle. Inbound shipping charges (from you to us) are the responsibility of the customer. We will pay the return freight.

LIMITATION OF LIABILITY
THE REMEDIES DESCRIBED ABOVE ARE YOUR SOLE AND EXCLUSIVE REMEDIES AND OUR ENTIRE LIABILITY FOR ANY BREACH OF THIS LIMITED WARRANTY. OUR LIABILITY SHALL UNDER NO CIRCUMSTANCES EXCEED THE ACTUAL AMOUNT PAID BY YOU FOR THE DEFECTIVE PRODUCT, NOR SHALL WE UNDER ANY CIRCUMSTANCES BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE DAMAGES OR LOSSES, WHETHER DIRECT OR INDIRECT. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

COPYRIGHT
©Copyright 2025. All rights reserved, TeraFlex Inc. Reproduction of this instruction document and/or any of its contents without written permission is strictly prohibited. TeraFlex® is a registered trademark of TeraFlex Inc.
TeraFlex Inc. reserves the right to update, discontinue, redesign, modify finish, part number or component build parts if deemed necessary without written notice. TeraFlex Inc., and any associated dealers are not responsible for misprints or typographical errors that may have inadvertently been made within this instruction sheet.

Please reach out to the TeraFlex customer service with any questions regarding the installation of products or the limited warranty.

TERAFLEX
5680 West Dannon Way
West Jordan, UT. 84081
Phone/801.713.3314
Fax/801.713.2313
www.teraflex.com